

ELECTRONIC VALVE SPECIFICATIONS

SPECIFICATION CV1506 ISSUE 7 DATED 23.2.53

AMENDMENT No. 1

Page 3. Outline Drawing

At foot of page insert the following note:

"NOTE. On finished valves allow an additional 0.1" for solder on both pins and top caps."

February, 1960.

N.16337

Royal Aircraft Establishment

Specification MOSA/CV1506 Issue 7 Dated 23.2.53 To be read in conjunction with K1004	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

→ Indicates a change

TYPE OF VALVE - Pentode CATHODE - Directly Heated- thuriated ENVELOPE - Glass-umetallised PROTOTYPE - 50/450A		<u>MARKING</u> See K1001/4	
<u>RATING</u>		<u>BASE</u>	
		USL4	
		<u>CONNECTIONS</u>	
		Note	
			Pin
			Electrode
			1
			2
			3
			4
			TC1
			TC2
			<u>DIMENSIONS</u>
			See Drawing on Page 3
<u>NOTES</u>			
A. These ratings apply up to a maximum frequency of 10 Mc/s.			
B. At $V_a = 3000$, $V_{g2} = 600$, $I_a = 200$ mA.			

CV1506

TESTS

Page 2

To be performed in addition to those applicable in K1001.

	Test Conditions						Test	Limits		No. Tested
								Min.	Max.	
a	See K1001 /AIII						<u>CAPACITANCES</u> (pF)			
							C _{ae}	-	30.0	2% (10)
							C _{ge}	-	50.0	
							C _{ag}	-	0.4	
	V _f (AC)	V _a	V _{g3}	V _{g2}	V _{g1}	I _a (mA)				
b	10.0	0	0	0		0	I _f (A)	12.4	13.6	100%
c	10.0	2500	0	600	-88	-	I _a (mA)	120	210	100%
d	10.0	2500	0	600	-88	-	I _{g2} as % of value of I _a found in 'c'	-	6%	100% or S
e	10.0	2500	0	600	-88 to -93	-	g _m (mA/V)	5.0	-	100%
f	10.0	2500	0	600	-	200	I _{g1} (μA) after 15 mins. There shall be no increase in I _{g1} during last 10 mins.	-	15.0	100%
g	10.0	1000	1000	1000	1000	-	Total space current (A)	7.5	-	100%
h	10.0	2500	+400 re- duced to -100	600	Set to give I _a = 200 when V _{g3} = 0	-	Reduction in I _a (mA)	30.0	-	100%

