

GENERAL POST OFFICE: E-IN-C (S)

Specification: G.P.O./CV2192/Issue 1 Dated: September, 1954. To be read in conjunction with K 1001	<u>SECURITY</u>	
	<u>Specification</u> Unclassified	<u>Valve</u> Unclassified

→ indicates a change

<u>TYPE OF VALVE</u> - Cathode Ray Tube <u>TYPE OF DEFLECTION</u> - Magnetic <u>TYPE OF FOCUS</u> - Magnetic <u>SCREEN</u> - WW5 <u>PROTOTYPE</u> - C102B			<u>MARKING</u> See K1001/4	
			<u>BASE</u> I.O	
<u>Rating</u>	<u>Note</u>	<u>Connexions</u>		
		<u>Pin</u>	<u>Electrode</u>	
Heater Voltage (V)	4.0	1	No connection	
Heater Current (A)	1.1	2	Heater	
Max Final Anode Voltage (kV)	17.0	3	No pin	
Max Heater-Cathode Voltage (V)	± 200	4	No pin	
		5	Grid	
		6	No pin	
		7	Heater	
		8	Cathode	
		S.C.	Anode	
<u>Capacitances</u> (pF)		<u>Side Contact</u> See K1001/A1/D5.1		
Cc - all (max)	9.0			
Cg - all (max)	8.0	<u>Dimensions</u> See Drawing. Page 4		

CV2192

T E S T S

To be performed in addition to those applicable in K.1001

	TEST CONDITIONS				TEST	Limits		No. Tested	Note
	Vh (V)	Va (kV)	Vg (V)	Ib (μ A)		Min.	Max.		
(a)	See K 1001/5A.13.				<u>Capacitances</u> (μ F) (i) Grid to all other electrodes (ii) Cathode to all other electrodes	5 6	8 9	5% (5)	
(b)	4.0	-	-	-	Ih (A)	0.9	1.1	100%	
(c)	4.0	15.0	Adjust for out-off	-	Vg (V)	-55	-105	100%	
(d)	4.0	15.0	Adjust	100	(i) Change in Vg from value in Test (C) (V) (ii) Line Width (mm) (iii) Focus Coil Current (mA) (iv) Within the range of Vg from out-off to that for Ib=100 A, the beam current shall increase continuously	25 - 18	40 0.3 22	100% 100% 100%	1
(e)	4.0	15.0	Value Obtained in test (C)	-	<u>Grid Insulation</u> (i) Leakage current (μ A) (ii) Increase in Voltmeter Reading	- -	5 100%	100%	
(f)	4.0	15.0	Any convenient value		<u>Useful Screen Area</u> Raster size (cm)	-	17 X 12.75	100%	
(g)	4.0	15.0	Adjust	100	(i) Screen blemishes have to be not worse than an agreed standard (ii) Visual Brightness (lamberts)	- 64	-	100% 100%	2
(h)	4.0	15.0	Near Out-off	-	Deviation of unfocused spot from centre of screen (mm)	-	12	100%	

CV2192/1/2

CV2192

TESTS

To be performed in addition to those applicable in K.1001

	TEST CONDITIONS				TEST	Limits		No. Tested	Note
	Vh (V)	Va (kV)	Vg (V)	Ib (μ A)		Min.	Max.		
j					<p>No bubbles or non-transparent blemishes in the glass face of the tube shall be greater than 0.04" (1mm) Dia. and the maximum number of bubbles and blemishes permissible shall be according to the following:-</p> <p>With the anode arm of the tube vertical, the area of the tube face covered by a centred 17 cm x 12.75 cm rectangle, with its short sides aligned with the radius passing through the anode arm, to within limits of $\pm 30^\circ$, shall be subject to bubble and blemish concentration limits of a mean density of 4 per sq. inch (4 per 6.25 sq. cm)</p> <p>This refers to bubbles in the size range 0.006" to 0.040" Dia. Bubbles below 0.006" are neglected, unless in sufficient concentration to produce "cloudiness".</p>			100%	
<u>NOTES</u>									
<p>1. The necessary focusing field is to be obtained from a coil as specified below, the centre of the coil to lie 11 cm from the AA reference line on the tube neck.</p> <p>Coil Specification outside diam. $3\frac{1}{2}$", inside diam. $1\frac{7}{8}$". Length $1\frac{1}{2}$". Windings 41,000 Turns of 42 SWG Enam. Copper. Outer edge and faces of coil shrouded with 1/16" Soft iron. Brass Core.</p> <p>2. Visual Brightness measured by an EEL Type Photo cell with filter, to correct response to eye sensitivity curve, held against tube face.</p> <p>Calibration of cell to be made by means of Air Ministry Test Set 139.</p>									

CV2192/1/3

