

10EM7

Dual Triode With High-Mu Unit and Low-Mu Unit

The 10EM7 is the same as the 6EM7 except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	9.7	volts
Warm-up time (Average)	11	sec

10GF7

Dual Triode With High-Mu Unit and Low-Mu Unit

NOVAR TYPE

The 10GF7 is the same as the 6GF7 except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	9.7	volts
Warm-up time (Average)	11	sec

10GF7A

Dual Triode With High-Mu Unit and Low-Mu Unit

NOVAR TYPE

The 10GF7A is the same as the 6GF7A except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	9.7	volts
Warm-up time (Average)	11	sec



10GN8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 10GN8 is the same as the 6GN8 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	10.5	volts
Warm-up time (Average)	11	sec

10HF8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 10HF8 is the same as the 6HF8 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	10.5	volts
Warm-up time (Average)	11	sec

