

15AF11

Dual Triode— Sharp-Cutoff Pentode

DUODECAR TYPE

The 15AF11 is the same as the 6AF11 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at 0.450 amp. | 14.7 | volts |
| Warm-up time (Average) | 11 | sec |

15BD11

Dual Triode— Sharp-Cutoff Pentode

DUODECAR TYPE

The 15BD11 is the same as the 6BD11 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at 0.450 amp. | 14.7 | volts |
| Warm-up time (Average) | 11 | sec |

15CW5

Beam Power Tube

The 15CW5 is the same as the 6CW5 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current | 0.300 ± 0.020 | amp |
| Voltage (AC or DC) at 0.300 amp. | 15.0 | volts |



15FM7

Dual Triode

DUODECAR TYPE

The 15FM7 is the same as the 6FM7 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at 0.450 amp. | 14.8 | volts |
| Warm-up time (Average) | 11 | sec |

15FY7

Dual Triode

DUODECAR TYPE

The 15FY7 is the same as the 6FY7 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at 0.450 amp. | 14.7 | volts |
| Warm-up time (Average) | 11 | sec |

15HB6

Power Pentode

The 15HB6 is the same as the 6HB6 except for the following items:

Heater Characteristics and Ratings:

| | | |
|--|---------------|-------|
| Current. | 0.300 ± 0.020 | amp |
| Voltage (AC or DC) at 0.300 amp. | 14.7 | volts |
| Warm-up time (Average) | 11 | sec |

