

# 19CG3

## Half-Wave Vacuum Rectifier

Duodecar Type

*The 19CG3 is the same as the 6CG3 except for:*

### Heater Characteristics and Ratings

Current . . . . .	0.600 $\pm$ 0.040 A
Voltage (ac or dc) at 0.600 A . . . . .	19.0 V
Warm-up time (Average) . . . . .	11 s

# 19CL8A

## Medium-Mu Triode— Sharp-Cutoff Tetrode

9-Pin Miniature Type

Controlled Heater Warm-up Time

*The 19CL8A is the same as the 6CL8A except for:*

### Heater Characteristics and Ratings

Current . . . . .	0.150 $\pm$ 0.010 A
Voltage (ac or dc) at 0.150 A . . . . .	18.9 V

# 19EA8

## Medium-Mu Triode— Sharp-Cutoff Pentode

9-Pin Miniature Type

Controlled Heater Warm-up Time

*The 19EA8 is the same as the 6EA8 except for:*

### Heater Characteristics and Ratings

Current . . . . .	0.150 $\pm$ 0.010 A
Voltage (ac or dc) at 0.150 A . . . . .	18.9 V



Electronic  
Components

DATA  
8-70

# 19FX5

## Power Pentode

### 7-Pin Miniature Type

*The 19FX5 is the same as the 60FX5 except for:*

#### Heater Characteristics and Ratings

Current . . . . .	0.300 $\pm$ 0.020 A
Voltage (ac or dc) at 0.300 A . . . . .	18.9 V
Warm-up time (Average) . . . . .	11 s

# 19HR6

## Semiremote-Cutoff Pentode

### 7-Pin Miniature Type

*The 19HR6 is the same as the 6HR6 except for:*

#### Heater Characteristics and Ratings

Current . . . . .	0.150 $\pm$ 0.010 A
Voltage (ac or dc) at 0.150 A . . . . .	18.9 V
Warm-up time (Average) . . . . .	17 s

# 19HS6

## Sharp-Cutoff Pentode

### 7-Pin Miniature Type

*The 19HS6 is the same as the 6HS6 except for:*

#### Heater Characteristics and Ratings

Current . . . . .	0.150 $\pm$ 0.010 A
Voltage (ac or dc) at 0.150 A . . . . .	18.9 V
Warm-up time (Average) . . . . .	17 s

