

(B3) C7

IB3-GT/8016 HALF-WAVE VACUUM RECTIFIER

Supersedes Type 8016

GENERAL DATA Electrical: Filament, Coated: Voltage. 1.25* ac volts Current. . 0.2 amp Direct Interelectrode Capacitance (Approx.): Plate to Filament. . . . μμf 1.5 * The filament voltage must never exceed 1.5 volts, even momentarily. • With no external shield. Mechanical: Mounting Position. . Any 3-7/8" ± 3/16' Overall Length . . 3-5/16" ± 3/16" Seated Length. . . 1-9/32" Maximum Diameter T-9 Bulb . Small Cap. . Intermediate-Shell Octal 6-Pin Basing Designation for BOTTOM VIEW . ц(5) Pin 7-Filament. Pin 1 - See NOTE Internal Pin 2-Filament Pin 3 - Same as Pin 1 Shield Pin 8 - Same as Pin 1 Pin 5 - Same as Pin 1 Cap -- Plate NOTE: May be connected to pin 7; otherwise, do not use. HALF-WAVE RECTIFIER Maximum Ratings. Design-Center Values: PEAK INVERSE PLATE VOLTAGE 30000 max. voltsl€ PEAK PLATE CURRENT 17 max. ma 2 max. AVERAGE PLATE CURRENT. ma FREQUENCY OF SUPPLY VOLTAGE. . . 300 max. kc OPERATING NOTES

when the filament is to be operated on rf, it is recommended that the filament be connected first to a dc or low-frequency ac supply of 1.25 volts. The color temperature of the filament corresponding to this voltage may then be checked visually by observing in a darkened room the reflection of the incandescent filament upon the upper surface of the internal shield. A visual comparison of this color temperature with that obtained with the filament operated from an rf voltage provides a convenient means for adjusting the amount of rf excitation to produce 1.25 volts (RMS) at the filament terminals.

The voltages employed in some television receivers and other high-voltage equipment are sufficiently high that high-voltage rectifier tubes may produce soft x-rays which can constitute a health hazard, unless such tubes are adequately shielded. Relatively simple shielding should prove adequate, but the need for this precaution should be considered in equipment design.

←Indicates a change.

DATA

183:51

IB3-GT

HALF-WAVE VACUUM RECTIFIER

