

# 22BH3

## Half-Wave Vacuum Rectifier

NOVAR TYPE

For TV Damper Service

*The 22BH3 is the same as the 6BH3 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	$I_h$	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450A. . .	$E_h$	22.4	V
Warm-up time (Average) . . . . .		11	s

# 22BH3A

## Half-Wave Vacuum Rectifier

NOVAR TYPE

For TV Damper Service

*The 22BH3A is the same as the 6BH3A except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	$I_h$	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450A. . .	$E_h$	22.4	V
Warm-up time (Average) . . . . .		11	s

# 22DE4

## Half-Wave Vacuum Rectifier

For TV Damper Service

*The 22DE4 is the same as the 6DE4 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	$I_h$	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450A. . .	$E_h$	22.4	V
Warm-up time (Average) . . . . .		11	s



# 22JF6

## Beam Power Tube

NOVAR TYPE

For Horizontal-Deflection-Amplifier Service  
in Low-B+, Black-and-White TV Receivers

*The 22JF6 is the same as the 6JF6 except for the following items:*

### Heater Characteristics and Ratings

Current. . . . .	$I_h$	$0.450 \pm 0.030$	A
Voltage (AC or DC) at 0.450A . . . . .	$E_h$	22.0	V
Warm-up time (Average) . . . . .		11	s

