

Picture Tube

PAN-O-PLY — INTEGRAL IMPLOSION PROTECTION

(Provided by Formed Rim and Welded Tension Bands around Periphery of Tube Panel—No Separate Safety-Glass or Integral Protective Window Required)

RECTANGULAR GLASS TYPE ALUMINIZED SCREEN
 LOW-VOLTAGE ELECTROSTATIC FOCUS 92° MAGNETIC DEFLECTION
 NO ION-TRAP MAGNET REQUIRED

Low-Grid-No.2-Voltage—for Cathode-Drive Operation

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes	5	pf
Grid No.1 to all other electrodes	6	pf
External conductive coating to anode ^a	{ 2500 max. 1700 min.	pf
Heater Current at 6.3 volts.	600 ± 30	ma
Heater Warm-up Time (Average).	11	seconds
Electron Gun. Type Requiring No Ion-Trap Magnet		

Optical:

Phosphor (For curves, see front of this Section)	P4-Sulfide Type,	Aluminized
Faceplate	Filterglass
Light transmission at center (Approx.).	42%	

Mechanical:

Weight (Approx.).	29 lbs
Overall Length.	18.125" ± .375"
Neck Length	5.625" ± .125"
Projected Area of Screen.	282 sq. in.

External Conductive Coating:


Type. Regular-Band
 Contact area for grounding. Near Reference Line
 For Additional Information on Coatings, Dimensions, and Deflection Angles:

See Picture-Tube Dimensional-Outlines and Bulb J187 J
 sheets at the front of this section.

Cap Recessed Small Cavity (JEDEC No. J1-21)
 Base. Short Small-Shell Duodecal 6-Pin,
 (JEDEC Group 4, No. B6-203)

Basing Designation for BOTTOM VIEW. 12L

- Pin 1 - Heater
- Pin 2 - Grid No.1
- Pin 6 - Grid No.4
- Pin 10 - Grid No.2
- Pin 11 - Cathode
- Pin 12 - Heater



- Cap - Anode
 (Grid No.3,
 Grid No.5,
 Screen,
 Collector)
- C - External
 Conductive
 Coating



23ENP4

Maximum and Minimum Ratings, Design-Maximum Values:

Unless otherwise specified, voltage values are positive with respect to grid No. 1

Anode Voltage	{ 25000 max. 11000 min.	volts
Grid-No.4 Voltage:		
Positive value	1250 max.	volts
Negative value	400 max.	volts
Grid-No.2 Voltage	{ 70 max. 40 min.	volts
Cathode Voltage:		
Negative peak value.	2 max.	volts
Negative bias value.	0 max.	volts
Positive bias value.	100 max.	volts
Positive peak value.	150 max.	volts
Heater Voltage	{ 6.9 max. 5.7 min.	volts
Peak Heater-Cathode Voltage:		
Heater negative with respect to cathode:		
During equipment warm-up period		
not exceeding 15 seconds	450 max.	volts
After equipment warm-up period	300 max.	volts
Heater positive with respect to cathode:		
Combined AC & DC voltage	200 max.	volts
DC Component	100 max.	volts

Typical Operating Conditions for Cathode-Drive Service:

Unless otherwise specified, voltage values are positive with respect to grid No. 1

Anode Voltage	20000	volts
Grid-No.4 Voltage ^b	200	volts
Grid-No.2 Voltage	50	volts
Cathode Voltage for visual extinction of focused raster	36 to 54	volts
Field Strength of required adjustable Centering Magnet	0 to 12	gauss

Maximum Circuit Value:

Grid-No.1 Circuit Resistance	1.5 max.	megohms
--	----------	---------

^a Includes implosion protection hardware.

^b The grid-No.4 voltage required for optimum focus of any individual tube will have a value anywhere between 0 and +400 volts with the combined grid-No.1 voltage and video-signal voltage adjusted to give an anode current of 200 microamperes on a 13-1/2-inch by 18-inch pattern from an RCA-2F21 monoscope, or equivalent.

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

