



25DN6

25DN6

## BEAM POWER TUBE

Intended for use in equipment having  
series heater-string arrangement

## GENERAL DATA

## Electrical:

Heater, for Unipotential Cathode:

Voltage . . . . .	25	ac or dc volts
Current . . . . .	0.6	amp
Warm-up time (Average) . . . . .	11	sec

For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.

Direct Interelectrode Capacitances (Approx.):<sup>0</sup>

Grid No.1 to plate . . . . .	0.8	$\mu\text{uf}$
Grid No.1 to cathode & grid No.3, grid No.2, and heater . . . . .	22	$\mu\text{uf}$
Plate to cathode & grid No.3, grid No.2, and heater . . . . .	11.5	$\mu\text{uf}$


Characteristics, Class A<sub>1</sub> Amplifier:

Plate Voltage . . . . .	50	125	volts
Grid-No.2 (Screen-Grid) Voltage . . . . .	100	125	volts
Grid-No.1 (Control-Grid) Voltage . . . . .	0	-18	volts
Mu Factor, Grid No.2 to Grid No.1 . . . . .	-	4.35	
Plate Resistance (Approx.) . . . . .	-	4000	ohms
Transconductance . . . . .	-	9000	$\mu\text{mhos}$
Plate Current . . . . .	240*	70	ma
Grid-No.2 Current . . . . .	30*	6.3	ma
Grid-No.1 Voltage (Approx.) for plate current of 0.5 ma . . . . .	-	-36	volts

## Mechanical:

Operating Position . . . . .	Vertical, base up or down, or Horizontal with pins 1 and 3 in vertical plane
Maximum Overall Length . . . . .	5"
Seated Length . . . . .	4-1/4" $\pm$ 3/16"
Maximum Diameter . . . . .	1-9/16"
Bulb . . . . .	T12
Cap . . . . .	Small (JETEC No.C1-1)
Base . . . . .	Short Medium-Shell Octal 8-Pin with External Barriers, Style B (JETEC No.B8-118)
Basing Designation for BOTTOM VIEW . . . . .	5BT

- Pin 1 - No Connection
- Pin 2 - Heater
- Pin 3 - Cathode, Grid No.3
- Pin 4 - No Connection



- Pin 5 - Grid No.1
- Pin 6 - No Connection
- Pin 7 - Heater
- Pin 8 - Grid No.2
- Cap - Plate

<sup>0,\*</sup>: See next page.



25DN6

## BEAM POWER TUBE

## HORIZONTAL DEFLECTION AMPLIFIER

## Maximum Ratings, Design-Center Values Except as Noted:

For operation in a 525-line, 30-frame system □

DC PLATE VOLTAGE . . . . .	700	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE (Absolute maximum)* . . . . .	6600	max.	volts
PEAK NEGATIVE-PULSE PLATE VOLTAGE . . . . .	1500	max.	volts
DC GRID-No.2 (SCREEN-GRID) VOLTAGE . . . . .	175	max.	volts
PEAK NEGATIVE-PULSE GRID-No.1 VOLTAGE . . . . .	200	max.	volts
CATHODE CURRENT:			
Peak . . . . .	700	max.	ma
Average. . . . .	200	max.	ma
GRID-No.2 INPUT. . . . .	3	max.	watts
PLATE DISSIPATION† . . . . .	15	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode. . . . .	200	max.	volts
Heater positive with respect to cathode. . . . .	200▲	max.	volts
BULB TEMPERATURE (At hottest point on bulb surface). . . . .	225	max.	°C

## Maximum Circuit Values:

## Grid-No.1-Circuit Resistance:

For grid-resistor-bias operation . . . 0.47 max. megohm

□ Without external shield.

\* These values can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.

□ As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.

■ This rating is applicable when the duration of the voltage pulse does not exceed 15 percent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

■ Under no circumstances should this absolute value be exceeded.

† It is essential that the plate dissipation be limited in the event of loss of grid-No.1 signal. For this purpose, some protective means such as a cathode resistor of suitable value should be employed.

▲ The dc component must not exceed 100 volts.



25DN6

25DN6

## BEAM POWER TUBE

