

4CS6

Pentagrid Amplifier

7-PIN MINIATURE TYPE

The 4CS6 is the same as the 6CS6 except for the following items:

Heater Characteristics and Ratings:

| | |
|---|-------------------|
| Current. | 0.450 ± 0.030 amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 volts |
| Warm-up time (Average) | 11 sec |

4CY5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

The 4CY5 is the same as the 6CY5 except for the following items:

Heater Characteristics and Ratings:

| | |
|---|-------------------|
| Current. | 0.300 ± 0.020 amp |
| Voltage (AC or DC) at heater amperes = 0.300 | 4.5 volts |
| Warm-up time (Average) | 11 sec |

4DE6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

The 4DE6 is the same as the 6DE6 except for the following items:

Heater Characteristics and Ratings:

| | |
|---|-------------------|
| Current. | 0.450 ± 0.030 amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 volts |
| Warm-up time (Average) | 11 sec |



4DK6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

The 4DK6 is the same as the 6DK6 except for the following items:

Heater Characteristics and Ratings:

| | | |
|---|---------------|-------|
| Current. | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 | volts |
| Warm-up time (Average) | 11 | sec |

4DT6A

Sharp-Cutoff Pentode

With Two Independent Control Grids

7-PIN MINIATURE TYPE

The 4DT6A is the same as the 6DT6A except for the following items:

Heater Characteristics and Ratings:

| | | |
|---|---------------|-------|
| Current. | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater amperes = 0.450 | 4.2 | volts |
| Warm-up time (Average) | 11 | sec |

