

4EH7

Semiremote-Cutoff Pentode

9-PIN MINIATURE TYPE

The 4EH7 is the same as the 6EH7 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	4.4	volts

4EJ7

Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 4EJ7 is the same as the 6EJ7 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450.	4.4	volts

4ES8

Variable-Mu Twin Triode

9-PIN MINIATURE TYPE

The 4ES8 is the same as the 6ES8 except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	4	volts
Warm-up time (Average)	11	sec



4EW6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

The 4EW6 is the same as the 6EW6 except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	4.2	volts
Warm-up time (Average)	11	sec

4GM6

Semiremote-Cutoff Pentode

7-PIN MINIATURE TYPE

The 4GM6 is the same as the 6GM6 except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	4.2	volts
Warm-up time (Average)	11	sec

