



50Y7-GT

# 50Y7-GT

## VACUUM RECTIFIER-DOUBLER


### GENERAL DATA

Electrical:	Without	With No. 40	
	Panel Lamp	or No. 47 Panel Lamp	
Heater, for Unipotential Cathode:			
Voltage (AC or DC):			
Entire Heater (pins 2 & 7)	50	46	volts
Panel-Lamp Section (pins 6 & 7)	7.5	5.5	volts
Current	between pins 2 & 7	0.15	amp
	between pins 2 & 6	-	0.15 amp

### Mechanical:

Mounting Position	Any
Maximum Overall Length	3-5/16"
Maximum Seated Length	2-3/4"
Maximum Diameter	1-9/32"
Bulb	T-9
Base	Intermediate-Shell Octal 8-Pin
Base Designation for BOTTOM VIEW	G-8AN

- Pin 1 - No Connection
- Pin 2 - Heater
- Pin 3 - Plate No. 2
- Pin 4 - Cathode No. 2



- Pin 5 - Plate No. 1
- Pin 6 - Heater Tap
- Pin 7 - Heater
- Pin 8 - Cathode No. 1

### RECTIFIER OR DOUBLER

### Maximum Ratings, Design-Center Values:

PEAK INVERSE PLATE VOLTAGE	700 max.	volts
PEAK PLATE CURRENT PER PLATE	450 max.	ma
DC OUTPUT CURRENT PER PLATE		
With Panel Lamp & {	No Shunting Resistor	60 max. ma
Without Panel Lamp {	Shunting Resistor*	65 max. ma
		75 max. ma
PANEL-LAMP-SECTION VOLTAGE (RMS):		
When panel lamp fails	15 max.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	350 max.	volts
Heater positive with respect to cathode	350 max.	volts

### Typical Operation with No.40 or No.47 Panel Lamp in Half-Wave Rectifier Circuit with Capacitor-Input Filter:

AC Plate-Supply Volt. per Plate (RMS)	117	150	235	volts
Filter-Input Capacitor	16	16	16	μf
Min. Total Effect. Plate-				
Supply Imped. per Plate	15	40	100	ohms
Panel Lamp Shunting Resistor	250	250	250	ohms
DC Output Current per Plate	65	65	65	ma

\* Max. value of this resistor is 250 ohms for dc output current of 65 ma.

50Y7-GT



50Y7-GT

## VACUUM RECTIFIER-DOUBLER

### Typical Operation with No.40 or No.47 Panel Lamp in Voltage-Doubler Circuit:

	Half-Wave	Full-Wave	
AC Plate Supply Voltage per Plate (RMS). . . . .	117	117	volts
Filter-Input Capacitor . . . . .	16	16	$\mu$ f
Min. Total Effect. Plate- Supply Imped. per Plate. . . . .	30	15	ohms
Panel Lamp Shunting Resistor . . .	250	250	ohms
DC Output Current per Plate. . . .	65	65	ma

### Typical Operation Without Panel Lamp in Half-Wave Rectifier Circuit with Capacitor-Input Filter:<sup>o</sup>

*Values are for both units connected in parallel*

AC Plate Supply Voltage (RMS). . . . .	117	150	235	volts
Filter-Input Capacitor . . . . .	16	16	16	$\mu$ f
Min. Total Effect. Plate- Supply Imped. per Plate. . . . .	15	40	100	ohms
Total DC Output Current. . . . .	150	150	150	ma
DC Output Voltage at Input to Filter (Approx.):				
At half-load current (75 ma.). . . .	115	-	255	volts
At full-load current (150 ma.) . . .	80	-	200	volts
Voltage Regulation (Approx.):				
Half-load to full-load current . . .	35	-	55	volts

### Typical Operation Without Panel Lamp in Full-Wave Voltage-Doubler Circuit:<sup>o</sup>

AC Plate Supply Voltage per Plate (RMS). . . . .	117	volts
Filter-Input Capacitor . . . . .	16	$\mu$ f
Min. Total Effective Plate- Supply Impedance per Plate . . . . .	15	ohms
DC Output Current. . . . .	75	ma
DC Output Voltage at Input to Filter (Approx.):		
At half-load current (37.5 ma.). . . . .	250	volts
At full-load current (75 ma.). . . . .	205	volts
Voltage Regulation (Approx.):		
Half-load to full-load . . . . .	45	volts

<sup>o</sup> Plate current must not flow through heater section between pins 6 and 7.