

# 5CG8

## Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CG8 is the same as the 6CG8A except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CL8A

## Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CL8A is the same as the 6CL8A except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CM8

## High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CM8 is the same as the 6CM8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp



# 5CQ8

---

## Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CQ8 is the same as the 6CQ8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CZ5

---

## Beam Power Tube

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CZ5 is the same as the 6CZ5 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp





5CG8

5CG8  
TO  
5CM8

## TRIODE-PENTODE CONVERTER

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 5CG8 is the same as the 6CG8 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp
Warm-up time (Average) . . . . .	11	sec

## 5CL8-A

### MEDIUM-MU TRIODE— SHARP-CUTOFF TETRODE

9-PIN MINIATURE TYPE

*Intended for use as combined VHF oscillator and mixer  
tube in TV receivers having series heater-string arrangement*

*The 5CL8-A is the same as the 6CL8-A except for the following  
items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

## 5CM8

### HIGH-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 5CM8 is the same as the 6CM8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

5CQ8  
5CZ5



5CQ8

**MEDIUM-MU TRIODE—  
SHARP-CUTOFF TETRODE**

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 5CQ8 is the same as the 6CQ8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

5CZ5

**BEAM POWER TUBE**

9-PIN MINIATURE TYPE

*For vertical-deflection-amplifier service in 110°  
systems having series heater-string arrangement*

*The 5CZ5 is the same as the 6CZ5 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CG8

## Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

*The 5CG8 is the same as the 6CG8-A except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CL8-A

## Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

*The 5CL8-A is the same as the 6CL8-A except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CM8

## High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

*The 5CM8 is the same as the 6CM8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp



# 5CQ8

---

## Medium-Mu Triode— Sharp-Cutoff Tetrode

### 9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

*The 5CQ8 is the same as the 6CQ8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

---

# 5CZ5

---

## Beam Power Tube

### 9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

*The 5CZ5 is the same as the 6CZ5 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

---

# 5EW6

---

## Sharp-Cutoff Pentode

### 7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

*The 5EW6 is the same as the 6EW6 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	5.6	volts
Current . . . . .	0.45 ± 6%	amp
Warm-up time (Average) . . . . .	11	sec

