

## Medium-Mu Triode— Sharp-Cutoff Pentode

### ELECTRICAL

#### Heater Characteristics and Ratings

Voltage (AC or DC) . . . . .	6.3 ± 0.6	V
Current at 6.3 V . . . . .	0.410	A
Heater-cathode voltage <sup>a</sup> . . . . .	110 max	V

#### Direct Interelectrode Capacitances (Approx.)

##### Triode Unit

P <sub>T</sub> to G <sub>T</sub> . . . . .	1.8	pF
G <sub>T</sub> to K, H . . . . .	3.3	pF
P <sub>T</sub> to all except G <sub>1p</sub> . . . . .	1.7	pF

##### Pentode Unit (With external shield)

Input . . . . .	6.2	pF
Output . . . . .	3.5	pF
P <sub>p</sub> to G <sub>1p</sub> . . . . .	0.009	pF
G <sub>1p</sub> to G <sub>2p</sub> . . . . .	1.5	pF

##### Between Triode and Pentode Units


P <sub>T</sub> to P <sub>p</sub> . . . . .	0.025 max	pF
P <sub>p</sub> to G <sub>T</sub> . . . . .	0.01 max	pF
P <sub>T</sub> to G <sub>1p</sub> . . . . .	0.01 max	pF
G <sub>T</sub> to G <sub>1p</sub> . . . . .	0.01 max	pF

### MECHANICAL

Operating Position . . . . .	Any
Type of Cathode . . . . .	Coated Unipotential
Maximum Overall Length . . . . .	2 in
Maximum Seated Length . . . . .	1-3/4 in
Diameter . . . . .	0.750 to 0.875 in
Envelope . . . . .	JEDEC T6-1/2
Base . . . . .	Small-Button Nova! 9-Pin (JEDEC No. E9-1)

#### TERMINAL DIAGRAM (Bottom View)

- Pin 1—Cathode, Pentode
- Grid No.3, Internal Shield
- Pin 2—Pentode Grid No.1
- Pin 3—Same as Pin 1
- Pin 4—Heater
- Pin 5—Heater
- Pin 6—Pentode Plate
- Pin 7—Pentode Grid No.2
- Pin 8—Triode Plate
- Pin 9—Triode Grid



9QA

### CHARACTERISTICS

	Triode Unit	Pentode Unit	
Plate Voltage . . . . .	100	170	V
Grid-No.2 Voltage . . . . .	-	120	V
Grid-No.1 Voltage . . . . .	-3	-1.2	V
Amplification Factor . . . . .	20	55 <sup>b</sup>	



	Triode Unit	Pentode Unit	
Plate Resistance (Approx.) . . . . .	-	0.35	MΩ
Transconductance . . . . .	9000	11000	μmhos
Plate Current. . . . .	15	10	mA
Grid No.2 Current. . . . .	-	3	mA

### DESIGN-MAXIMUM RATINGS

	Triode Unit	Pentode Unit	
Plate-Supply Voltage . . . . .	600	600	V
DC Plate Voltage . . . . .	140	275	V
Grid-No.2 Supply Voltage . . . . .	-	600	V
DC Grid-No.2 (Screen-Grid) Voltage . .	-	275	V
DC Grid-No.1 (Control-Grid) Voltage. .	-	-50	V
Cathode Current. . . . .	22	20	mA
Plate Dissipation. . . . .	1.8	2.4	W
Grid-No.2 Input <sup>c</sup> . . . . .	-	0.55	W

### MAXIMUM CIRCUIT VALUES

#### Grid-No.1-Circuit Resistance

For fixed-bias operation . . . . .	0.5	1	MΩ
For cathode-bias operation . . . . .	0.5	2.2	MΩ

<sup>a</sup> The hum should be minimized in intercarrier receiver applications by limiting the heater-cathode voltage to 100 volts rms, and in AM receivers to 50 volts rms.

<sup>b</sup> Grid No.2 to grid No.1; approximate value.

<sup>c</sup> When control grid bias is between -1.5 and -2 volts, screen dissipation is limited to 0.50 watt. When this bias is greater than -2 volts, maximum screen dissipation is 0.36 watt.

