

Pentode—Beam Power Tube

DUODECAR TYPE

For Combined Limiter, Discriminator, and Audio Power
Output Applications in FM Radio and TV Receivers

ELECTRICAL CHARACTERISTICS

Bogey Values

Heater Voltage	E_h	6.3	V
Heater Current	I_h	0.950	A
Direct Interelectrode Capacitances			
Without external shield			
<i>Pentode Unit:</i>			
G_{1p} to G_{3p}	C_{g1-g3}	0.009	pF
G_{1p} to ($K_p + 1S, P_p, G_{3p}, G_{2p}, H$) . . .	C_{g1-all}	4.4	pF
G_{3p} to ($K_p + 1S, P_p, G_{2p}, G_{1p}, H$) . . .	C_{g3-all}	3.2	pF
<i>Beam Power Unit:</i>			
G_{1B} to P_B	C_{g1-p}	0.22	pF
Input: G_{1B} to ($K_B + G_{3B}, G_{2B}, H$) . . .	C_i	11	pF
Output: P_B to ($K_B + G_{3B}, G_{2B}, H$) . . .	C_o	7.5	pF

Pentode Unit

For the following characteristics, see Conditions

Transconductance, Grid No.1				
to Plate	g_m	- -	360	μ mho
Transconductance, Grid No.3				
to Plate	$g_m(g_{3-p})$	- -	700	μ mho
DC Plate Current	I_b	-	5	mA
DC Grid-No.2 Current	I_{c2}	4.5	-	mA
Cutoff DC Grid-No.1 Voltage for				
$I_b = 20 \mu A$	$E_{c1(co)}$	-	-	-4
Cutoff DC Grid-No.3 Voltage for				
$I_b = 20 \mu A$	$E_{c3(co)}$	-	-	-4

Conditions

Heater Voltage	E_h	Bogey value			V
DC Plate Voltage	E_b	135	135	135	V
DC Grid-No.3 Voltage	E_{c3}	4	4	0	V
DC Grid-No.2 Supply Voltage	E_{cc2}	-	280	280	V
DC Grid-No.2 Voltage	E_{c2}	75	-	-	V
DC Grid-No.1 Voltage	E_{c1}	0	0	0	V
Grid-No.2 Resistor	R_{g2}	-	33	33	k Ω

Beam Power Unit

For the following characteristics, see Conditions

Plate Resistance (Approx.)	r_p	100	k Ω	
Transconductance	g_m	6500	μ mho	
DC Plate Current	I_b	35	mA	
DC Grid-No.2 Current	I_{c2}	3	mA	

Conditions

Heater Voltage	E_h	Bogey value			V
DC Plate Voltage	E_b	250	V		
DC Grid-No.2 Voltage	E_{c2}	250	V		
DC Grid-No.1 Voltage	E_{c1}	-8	V		




MECHANICAL CHARACTERISTICS

Operating Position	Any
Type of Cathodes	Coated Unipotential
Maximum Overall Length	2.375 in
Maximum Seated Length	2.000 in
Maximum Diameter	1.188 in
Dimensional Outline (JEDEC 9-58)	See General Section
Envelope	JEDEC T9
Base	Small-Button Duodecar 12-Pin (JEDEC E12-70)

TERMINAL DIAGRAM (Bottom View)

- Pin 1 - Heater
- Pin 2 - Beam Power Grid No.2
- Pin 3 - Beam Power Cathode,
Beam Power Grid No.3
- Pin 4 - Pentode Plate
- Pin 5 - Pentode Grid No.3
- Pin 6 - Pentode Grid No.2
- Pin 7 - Pentode Grid No.1
- Pin 8 - Pentode Cathode,
Internal Shields
- Pin 9 - Beam Power Plate
- Pin 10 - No Internal Connection
- Pin 11 - Beam Power Grid No.1
- Pin 12 - Heater



DESIGN-MAXIMUM RATINGS

Pentode Unit for FM and TV Limiter and Discriminator Service; Beam Power Unit for Audio Power Output Service

		Pentode Unit	Beam Power Unit	
DC Plate Supply Voltage.	E_{bb}	330	-	V
DC Plate Voltage	E_b	-	275	V
DC Grid-No.2 (Accelerator- Grid) Supply Voltage.	E_{cc2}	330	-	V
DC Grid-No.2 (Screen-Grid) Voltage	E_{c2}	-	275	V
Peak Positive-Pulse Grid- No.1 (Limiter-Grid) Voltage	e_{c1m}	60	-	V
Heater-Cathode Voltage:				
Peak	e_{hkm}	±200	±200	V
DC	E_{hk}	100	100	V
Heater Voltage (AC or DC).	E_h	← 5.7 to 6.9 →		V
Average Cathode Current.	$I_{k(av)}$	13	-	mA
Grid-No.2 Input.	P_{g2}	-	2	W
Plate Dissipation.	P_b	-	10	W

MAXIMUM CIRCUIT VALUES

Beam Power Unit

Grid-No. 1-Circuit Resistance:	$R_{g1(ckt)}$	
For fixed-bias operation	-	0.25 MΩ
For cathode-bias operation	-	0.5 MΩ



TYPICAL OPERATION

Beam Power Unit

		Bogey value	
Heater Voltage	E_h		V
DC Plate Voltage	E_b	250	V
DC Grid-No.2 Voltage	E_{c1}	250	V
DC Grid-No.1 Voltage	E_{c2}	-8	V
Peak AF Grid-No.1 Voltage	e_{c1m}	8	V
Plate Resistance (Approx.)	r_p	100	$k\Omega$
Transconductance	g_m	6500	μmho
Zero-Signal Plate Current	I_b	35	mA
Maximum-Signal Plate Current	I_b	39	mA
Zero-Signal Grid-No.2 Current	I_{c2}	3	mA
Maximum-Signal Grid-No.2 Current	I_{c2}	13	mA
Load Resistance	R_L	5000	Ω
Total Harmonic Distortion		8.5	%
Maximum-Signal Power Output	P_o	4.2	W

