



COMPACTRON DIODE

FOR TV DAMPING DIODE APPLICATIONS

DESCRIPTION AND RATING

The 6BJ3 is a compactron containing a single heater-cathode type diode. It is intended for service as the damping diode in the horizontal-deflection circuit of television receivers.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC* 6.3±0.6	Volts
Heater Current†1.2	Amperes

Direct Interelectrode Capacitances, approximate‡

Cathode to Plate and Heater:		
k to (p + h)8.0	pf
Plate to Cathode and Heater:		
p to (k + h)5.5	pf
Heater to Cathode: (h to k)2.7	pf

MECHANICAL

Operating Position - Any

Envelope - T-9, Glass

Base - E12-70, Button 12-Pin

Outline Drawing - EIA 9-59

Maximum Diameter 1.188	Inches
Maximum Over-all Length 2.625	Inches
Maximum Seated Height 2.250	Inches


MAXIMUM RATINGS

Design-Maximum ratings are limiting values of operating and environmental conditions applicable to a bogey electron tube of a specified type as defined by its published data and should not be exceeded under the worst probable conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube, making allowance for the effects of changes in operating conditions due to variations in the characteristics of the tube under consideration.

The equipment manufacturer should design so that initially and throughout life no design-maximum value for the intended service is exceeded with a bogey tube under the worst probable operating conditions with respect to supply-voltage variation, equipment component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in the characteristics of all other electron devices in the equipment.

PHYSICAL DIMENSIONS




EIA 9-59

TERMINAL CONNECTIONS

- Pin 1 - Heater
- Pin 2 - No Connection
- Pin 3 - No Connection
- Pin 4 - Plate
- § Pin 5 - No Connection
- § Pin 6 - No Connection
- Pin 7 - Cathode
- § Pin 8 - No Connection
- § Pin 9 - No Connection
- Pin 10 - Plate
- Pin 11 - No Connection
- Pin 12 - Heater

BASING DIAGRAM



EIA 12BL

MAXIMUM RATINGS (Cont'd)

TV DAMPER SERVICE-DESIGN-MAXIMUM VALUES †

Peak Inverse Plate Voltage.	3300	Volts
Plate Dissipation.	4.0	Watts
Steady-State Peak Plate Current	840	Milliamperes
DC Output Current.	140	Milliamperes
Heater-Cathode Voltage		
Heater Positive with Respect to Cathode		
DC Component	100	Volts
Total DC and Peak.	300	Volts
Heater Negative with Respect to Cathode		
DC Component	600	Volts
Total DC and Peak.	3300	Volts

AVERAGE CHARACTERISTICS

Tube Voltage Drop		
I _b = 250 Milliamperes DC	21	Volts


FOOTNOTES

- * The equipment designer should design the equipment so that heater voltage is centered at the specified bogey value, with heater supply variations restricted to maintain heater voltage within the specified tolerance.
- † Heater current of a bogey tube at E_f = 6.3 volts.
- ‡ Without external shield.
- § Socket terminals 5, 6, 8, and 9 should not be used as tie points.
- ¶ For operation in a 525-line, 30-frame television system as described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission. The duty cycle of the voltage pulse must not exceed 15 percent of one scanning cycle.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an

express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

AVERAGE PLATE CHARACTERISTICS



RECEIVING TUBE DEPARTMENT
GENERAL ELECTRIC
 Owensboro, Kentucky