



TUNG-SOL



BEAM PENTODE
MINIATURE TYPE
COATED UNIPOTENTIAL CATHODE

HEATER
25±10% VOLTS 0.30 AMP.
AC OR DC

ANY MOUNTING POSITION
FOR SERIES STRING



THE 25C5 IS A HEATER-CATHODE TYPE, BEAM PENTODE OF MINIATURE CONSTRUCTION DESIGNED FOR USE AS A POWER AMPLIFIER IN THE OUTPUT STAGE OF AC-DC RECEIVERS. EXCEPT FOR HEATER RATINGS THE 25C5 IS IDENTICAL TO THE 50C5.

DIRECT INTERELECTRODE CAPACITANCES — APPROX.
WITH NO EXTERNAL SHIELD

GRID TO PLATE: G_1 TO P	0.6	$\mu\mu f$
INPUT: G_1 TO (H+K ₁ +G ₃ +G ₂)	13.0	$\mu\mu f$
OUTPUT: P TO (H+K ₁ +G ₃ +G ₂)	8.5	$\mu\mu f$

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER CURRENT	300±20	MA.
MAXIMUM HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DC AND PEAK	200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE		
DC	100	VOLTS
DC AND PEAK	200	VOLTS
MAXIMUM PLATE VOLTAGE	150	VOLTS
MAXIMUM GRID #2 VOLTAGE	130	VOLTS
MAXIMUM PLATE DISSIPATION	7	WATTS
MAXIMUM GRID #2 DISSIPATION	1.4	WATTS
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE:		
FIXED BIAS	0.1	MEGOHM
CATHODE BIAS	0.5	MEGOHM
MAXIMUM BULB TEMPERATURE (AT HOTTEST POINT ON BULB SURFACE)	220	°C

ALL ELECTRICAL DATA EXCEPT HEATER CHARACTERISTICS FOR TYPE 25C5 ARE IDENTICAL WITH THOSE OF TYPES 22C5, 22C5S, 17C5, 50C5 AND 50B5.

→ INDICATES A CHANGE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A_1 AMPLIFIER

PLATE VOLTAGE	120	VOLTS
GRID #2 VOLTAGE	110	VOLTS
GRID #1 VOLTAGE	-8	VOLTS
PEAK AF GRID #1 VOLTAGE	8	VOLTS
ZERO-SIGNAL PLATE CURRENT	49	MA.
ZERO-SIGNAL GRID #2 CURRENT	4	MA.
MAXIMUM SIGNAL PLATE CURRENT	50	MA.
MAXIMUM SIGNAL GRID #2 CURRENT	8.5	MA.
PLATE RESISTANCE (APPROX.)	10 000	OHMS
TRANSCONDUCTANCE	7 500	μ MHOS
LOAD RESISTANCE	2 500	OHMS
TOTAL HARMONIC DISTORTION	10	PERCENT
MAXIMUM SIGNAL POWER OUTPUT	2.3	WATTS

