



TUNG-SOL

PENTODE

MINIATURE TYPE

OUTLINE DRAWING
JEDEC 5-2BASE 7 PIN BUTTON
JEDEC E7-1FOR
FM SOUND DETECTOR
SERVICECOATED UNIPOTENTIAL CATHODE
ANY MOUNTING POSITIONBASING DIAGRAM
JEDEC 7EN

BOTTOM VIEW

THE 6GX6 IS A SHARP-CUTOFF PENTODE WITH DUAL CONTROL GRIDS IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED PRIMARILY FOR FM SOUND DETECTOR - SERVICE. EXCEPT FOR HEATER CHARACTERISTICS AND RATINGS, THE 6GX6 IS IDENTICAL TO THE 5GX6.

DIRECT INTERELECTRODE CAPACITANCES WITHOUT EXTERNAL SHIELD

GRID 1 TO PLATE	0.26	pf
GRID 1 TO (K & I.S., G3, G2, H)	8	pf
GRID 1 TO GRID 3	0.12	pf
GRID 3 TO PLATE	1.6	pf
GRID 3 TO (K & I.S., P, G2, G1, H)	6.5	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3 VOLTS	450	mA
HEATER WARM - UP TIME - AVERAGE		11	SECONDS
LIMITS OF APPLIED VOLTAGE - AC OR DC	6.3 ± .6		VOLTS
LIMITS OF SUPPLIED CURRENT - AC OR DC	450 ± 30		mA
PEAK HEATER - CATHODE VOLTAGE:			
HEATER POSITIVE WITH RESPECT TO CATHODE		200	VOLTS
DC COMPONENT		100	VOLTS
HEATER NEGATIVE WITH RESPECT TO CATHODE		200	VOLTS

CONTINUED ON FOLLOWING PAGE

CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS
DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

FM SOUND DETECTOR SERVICE

PLATE VOLTAGE	300	VOLTS
GRID 3 VOLTAGE:		
NEGATIVE VALUE - DC AND PEAK	100	VOLTS
POSITIVE VALUE - DC AND PEAK	25	VOLTS
GRID 2 SUPPLY VOLTAGE	300	VOLTS
GRID 2 VOLTAGE	SEE RATING CHART	
GRID 1 VOLTAGE:		
NEGATIVE - BIAS VALUE	50	VOLTS
POSITIVE - BIAS VALUE	0	VOLTS
GRID 3 INPUT	0.1	WATT
GRID 2 INPUT - UP TO 150 VOLTS	1	WATT
- BETWEEN 150 VOLTS AND 300 VOLTS	SEE RATING CHART	
PLATE DISSIPATION	1.7	WATTS
GRID 3 CIRCUIT RESISTANCE	0.68	MEGOHM
GRID 1 CIRCUIT RESISTANCE:		
FOR FIXED - BIAS OPERATION	0.22	MEGOHM
FOR CATHODE - BIAS OPERATION	0.47	MEGOHM

CHARACTERISTICS

CLASS A₁ AMPLIFIER

PLATE SUPPLY VOLTAGE	150	VOLTS
GRID 3 SUPPLY VOLTAGE	0	VOLTS
GRID 2 SUPPLY VOLTAGE	100	VOLTS
GRID 1 SUPPLY VOLTAGE	0	VOLTS
CATHODE RESISTOR	180	OHMS
PLATE CURRENT	3.7	mA
GRID 2 CURRENT	3.0	mA
TRANSCONDUCTANCE - GRID 1 TO PLATE	3,700	μ MHOS
TRANSCONDUCTANCE - GRID 3 TO PLATE	750	μ MHOS
PLATE RESISTANCE	APPROX. 0.14	MEGOHM
GRID 1 VOLTAGE FOR $I_b = 20 \mu A$	APPROX. -4.5	VOLTS
GRID 3 VOLTAGE FOR $I_b = 20 \mu A$	APPROX. -7	VOLTS

