



Excellence in Electronics

The 6C4W is a heater-cathode type medium-mu triode of miniature construction, suitable for use as a class C amplifier and oscillator. It is designed for dependable operation under conditions of shock and vibration usually found in mobile and aircraft applications.

MECHANICAL DATA

ENVELOPE: T-5 1/2 Glass

BASE: Miniature Button 7-Pin



TERMINAL CONNECTIONS:

- Pin 1 Plate, Pin 2 Internal Connection, Pin 3 Heater, Pin 4 Heater, Pin 5 Plate, Pin 6 Grid, Pin 7 Cathode

MECHANICAL RATINGS:

Maximum Impact Acceleration (Note 1) 450 G, Minimum Intermittent Heater Voltage Cycles (Note 2) 2000

MOUNTING POSITION: Any



BOTTOM VIEW

6BG

ELECTRICAL DATA

HEATER CHARACTERISTICS:

Heater Voltage 6.3 ± 10% volts, Heater Current 0.15 amps, Heater-Cathode Voltage: 100 volts (negative), 100 volts (positive)

DIRECT INTERELECTRODE CAPACITANCES: (pfd.s.)

Table with columns: With Shield, Without Shield. Rows: Grid to Plate, Input, Output.

RATINGS - ABSOLUTE MAXIMUM VALUES:

Table comparing Class A1 Amplifier and Class C Amplifier ratings for Plate Voltage, Grid Voltage, Plate Current, Grid Current, Plate Dissipation, Minimum External Grid-Bias Voltage, Grid Circuit Resistance, Fixed Bias, and Cathode Bias.

CHARACTERISTICS AND TYPICAL OPERATION - CLASS A1 AMPLIFIER:

Table showing typical operating values for Class A1 Amplifier: Plate Voltage (100), Grid Voltage (0), Plate Resistance (5900), Transconductance (3300), Amplification Factor (19.5), Plate Current (11.8).

* External shield #316 connected to pin.


Note 1: Forces in any direction as applied by the Navy type High Impact Machine for Electronic Devices.

Note 2: As checked at Ef=7.5 volts ac, on one minute and off one minute.



TRIODE

AVERAGE PLATE CHARACTERISTICS




RAYTHEON MANUFACTURING COMPANY

RECEIVING AND CATHODE RAY TUBE OPERATIONS




TRIODE

AVERAGE PLATE CHARACTERISTICS





TRIODE




RAYTHEON MANUFACTURING COMPANY

RECEIVING AND CATHODE RAY TUBE OPERATIONS



TRIODE

AVERAGE CHARACTERISTICS



RAYTHEON MANUFACTURING COMPANY

RECEIVING AND CATHODE RAY TUBE OPERATIONS