

CHARACTERISTICS

GENERAL DATA

Focusing Method	Electrostatic
Deflection Method	Magnetic
Deflection Angles (Approx.)	
Horizontal	81 Degrees
Diagonal	92 Degrees
Vertical	67 Degrees
Phosphor	Aluminized P4
Fluorescence	White
Persistence	Short to Medium
Faceplate	Bonded Shield
(Gray Filter Glass Safety Plate Laminated Directly to Face of Tube)	
Light Transmittance of Faceplate Assembly (Approx.)	44 Percent
External Surface Treated to Reduce Specular Reflection	

ELECTRICAL DATA

Heater Voltage	6.3 Volts	
Heater Current	$0.60 \pm 5\%$ Ampere	
Heater Warm-up Time ¹	11 Seconds	
Direct Interelectrode Capacitances (Approx.)		
Cathode to All Other Electrodes	5 $\mu\mu\text{f}$	
Grid No. 1 to All Other Electrodes	6 $\mu\mu\text{f}$	
External Conductive Coating to Anode ²	1700 $\mu\mu\text{f}$ Max.	
	1400 $\mu\mu\text{f}$ Min.	

MECHANICAL DATA

Minimum Useful Screen Dimensions (Maximum Assured)	
Height	12 $\frac{1}{16}$ Inches
Width	15 $\frac{1}{4}$ Inches
Diagonal	17 $\frac{5}{8}$ Inches
Area	172 Sq. Inches
Neck Length	5 $\frac{1}{2} \pm \frac{3}{16}$ Inches
Overall Length	15 $\frac{1}{2} \pm \frac{3}{8}$ Inches
Bulb	J149D
Safety Plate	FP159B
Bulb Contact (Recessed Small Cavity Cap)	J1-21
Base	B6-203
Basing	12L
Weight (Approx.)	20 Pounds



RATINGS

MAXIMUM RATINGS (Design Maximum Values) Grid Drive Service

Maximum Anode Voltage	20,000 Volts	dc
Minimum Anode Voltage	11,000 Volts	dc
Grid No. 4 Voltage (Focusing Electrode)	-550 to +1100 Volts	dc
Grid No. 2 Voltage	550 Volts	dc
Grid No. 1 Voltage		
Negative Bias Value	155 Volts	dc
Negative Peak Value	220 Volts	
Positive Bias Value	0 Volts	dc
Positive Peak Value	2 Volts	
Peak Heater-Cathode Voltage		
Heater Negative with Respect to Cathode		
During Warm-up Period not to Exceed 15 Seconds	450 Volts	
After Equipment Warm-up Period	200 Volts	
Heater Positive with Respect to Cathode	200 Volts	

QUICK REFERENCE DATA

Television Picture Tube
 19" Direct Viewed
 Rectangular Glass Type
 Bonded Shield
 Gray Filter Glass
 Anti-Reflection Treated
 Aluminized Screen
 Electrostatic Focus
 92° Magnetic Deflection
 No Ion Trap
 External Conductive Coating



12-L

SYLVANIA
 ELECTRONIC TUBES

A Division of
 Sylvania Electric Products Inc.

PICTURE TUBE
 OPERATIONS

SENECA FALLS, NEW YORK

Prepared and Released By The
 TECHNICAL PUBLICATIONS SECTION
 EMPORIUM, PENNSYLVANIA

MARCH, 1962

PAGE 1 OF 2

File Under

TELEVISION PICTURE TUBES

TYPICAL OPERATING CONDITIONS, Grid Drive Service

Anode Voltage	16,000 Volts	dc
Grid No. 4 Voltage for Focus	0 to +400 Volts	dc
Grid No. 2 Voltage	300 Volts	dc
Grid No. 1 Voltage Required for Cutoff ³	-35 to -72 Volts	dc

CIRCUIT VALUES

Grid No. 1 Circuit Resistance	1.5 Megohms Max.
---	------------------

NOTES:

1. Heater warm-up time is defined as the time required for the voltage across the heater to reach 80 % of the rated heater voltage after applying four (4) times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to three (3) times the rated heater voltage divided by the rated heater current.
2. External conductive coating must be grounded.
3. Visual extinction of focused raster. Extinction of stationary focused spot will require that these values be about 5 volts more negative.

WARNING:

X-ray radiation shielding may be necessary to protect against possible danger of personal injury from prolonged exposure at close range if this tube is operated at higher than the manufacturer's Maximum Rated Anode Voltage or 16,000 volts, whichever is less.

OUTLINE




DIAGRAM NOTES:

1. Reference line is determined by plane C-C' of JEDEC No. 116 Reference Line Gauge, when the gauge is seated against the bulb.
2. Base pin No. 6 aligns with horizontal centerline (A-A') within 30° and is on same side as anode contact, J1-21.
3. Planes perpendicular to the tube axis and passing through points X, Y, and Z are as follows:
 - Plane tangent to crown of face to plane of X: 0.500 nom.
 - Plane of X to plane of Y: 0.421" ± .025"
 - Plane of X to plane of Z: 0.738" ± .045"
4. Dimensions are in inches.