

RCA-6HB7

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-Pin Miniature Type
RCA Dark Heater **For UHF Oscillator-Mixer Service** **Controlled Heater Warm-up Time**
in TV Receivers

RCA-6HB7 is a multiunit tube of the 9-pin miniature type containing a medium-mu triode and a sharp-cutoff pentode in one envelope. This type is useful as a combined oscillator-mixer tube in television receivers utilizing an intermediate frequency in the order of 40 Mc.

The pentode unit of the 6HB7 has a relatively high value of transconductance and an excellent knee-current characteristic. In addition, the pentode unit has an exceptionally low value of grid-No.1-to-plate capacitance (0.010 pf maximum) to minimize feedback problems.

Two base pin connections to the cathode minimize the cathode lead inductance of the pentode unit. An inter-unit shield reduces interaction between units.

The heater of the 6HB7 has controlled warm-up time for use in series-heater-string arrangements. The RCA Dark Heater is utilized for long life and dependable performance.

Characteristics, Class A₁ Amplifier:

	Triode Unit	Pentode Unit	
Plate Supply Voltage.	150	125	volts
Grid-No.2 Supply Voltage.	-	125	volts
Grid-No.1 Supply Voltage.	0	-1	volts
Cathode Resistor.	56	-	ohms
Amplification Factor.	40	-	
Plate Resistance (Approx.).	5000	200,000	ohms
Transconductance.	8500	6400	μmhos
Plate Current	18	12	ma
Grid-No.2 Current	-	4	ma
Grid-No.1 Voltage (Approx.) for plate μ _a = 10	-12	-9	volts

Mechanical:

Operating Position.	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length.	2-3/16"
Maximum Seated Length	1-15/16"
Length, Base Seat to Bulb Top (Excluding Tip)	1-9/16" ± 3/32"
Diameter.	0.750" to 0.875"
Dimensional Outline	JEDEC No.6-2
Bulb.	T6-1/2
Base.	Small-Button Noval 9-Pin (JEDEC No.E9-1)

GENERAL DATA

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC).	6.3 ^a	volts
Current	0.450 ± 0.030	amp
Warm-up time (Average).	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 ^b max.	volts

Direct Interelectrode Capacitances:^c

Triode Unit:

Grid to plate	1.9	pf
Grid to cathode & pentode grid No.3 & internal shield, and heater.	3.0	pf
Plate to cathode & pentode grid No.3 & internal shield, and heater.	1.9	pf

Pentode Unit:

Grid No.1 to plate.	0.010 max.	pf
Grid No.1 to cathode & grid No.3 & internal shield, grid No.2, and heater.	5.0	pf
Plate to cathode & grid No.3 & internal shield, grid No.2, and heater.	3.4	pf
Heater to cathode ^d	3.8	pf

AMPLIFIER – Class A₁

Maximum Ratings, Design-Maximum Values:


	Triode Unit	Pentode Unit	
Plate Voltage	330 max.	330 max.	volts
Grid-No.2 (Screen-Grid) Supply Voltage.	-	330 max.	volts
Grid-No.2 Voltage	-	See Grid-No.2 Input Rating Chart	
Grid-No.1 (Control-Grid) Voltage:			
Positive-bias value	0 max.	0 max.	volts
Grid-No.2 Input:			
For grid-No.2 voltages up to 165 volts.	-	0.55 max.	watt
For grid-No.2 voltages between 165 and 330 volts	-	See Grid-No.2 Input Rating Chart	
Plate Dissipation	2.5 max.	3.1 max.	watts

Maximum Circuit Values:



Grid-No.1 Circuit Resistance:			
For fixed-bias operation.	0.5 max.	0.25 max.	megohm
For cathode-bias operation.	1.0 max.	0.5 max.	megohm

- ^a At heater amperes = 0.450.
- ^b The dc component must not exceed 100 volts.
- ^c With external shield JEDEC No.315 connected to cathode except as noted.
- ^d With external shield JEDEC No.315 connected to ground.


GRID-No.2-INPUT RATING CHART




AVERAGE CHARACTERISTICS
Triode Unit



AVERAGE CHARACTERISTICS
Pentode Unit




92CM-9867RI



92CM-9868RI

Information furnished by RCA is believed to be accurate and reliable. However, no responsibility is assumed by RCA for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of RCA.

**DIMENSIONAL OUTLINE
JEDEC No.6-2**




92CS-11893

Dimensions in Inches

- * Measured from base seat to bulb-top line as determined by ring gauge of 7/16" inside diameter.
 ** Applies in zone starting 0.375" from base seat.

TERMINAL DIAGRAM

Bottom View



JEDEC 9QA

- | | |
|-----------------------------------------------------------------|------------------------------|
| Pin 1 - Cathode,
Pentode
Grid No.3,
Internal
Shield | Pin 5 - Heater |
| Pin 2 - Pentode
Grid No.1 | Pin 6 - Pentode
Plate |
| Pin 3 - Same as
Pin 1 | Pin 7 - Pentode
Grid No.2 |
| Pin 4 - Heater | Pin 8 - Triode
Plate |
| | Pin 9 - Triode
Grid |