

HIGH VACUUM RECTIFIER

A296

June 1962

Page 1

ENGLISH ELECTRIC

INTRODUCTION

The A296 is a high vacuum rectifier with maximum ratings of 25kV peak inverse voltage and 6.5A peak anode current. It is designed for use in three phase rectifier circuits, giving a d.c. output of 3.0A at 23kV.

GENERAL DATA

Electrical

Filament	Thoriaated	Tungsten
Filament Voltage	6.3	V
Filament Current	32.5	A
Maximum Peak Inverse Voltage	25	kV
Maximum Anode Current:							
Peak	6.5	A
Mean	1.25	A
Maximum Anode Dissipation:							
Natural Cooling	375	W
Forced-air Cooling	500	W
Nominal Impedance (at 3.0A)	130	Ω

Mechanical

Overall Length	9.85	inches	(250	mm)	Max
Overall Diameter	5.20	inches	(132.1	mm)	Max
Net Weight	1.5	pounds	(0.68	kg)	Approx
Base	Flying Leads
Mounting Position	Vertical, base down Use bulb supporting ring
Maximum Bulb Temperature	350	°C
Maximum Anode or Base Seal Temperature	220	°C

A top cap radiator, with a minimum surface area of 8sq.in. perpendicular to the axis of the valve, should be used. The radiator should make good thermal contact with the entire length of the anode terminal.


X-RAY WARNING

X-rays are produced when the A296 is operated with a peak inverse anode voltage above 16kV (absolute value). These rays can constitute a health hazard unless the valve is adequately shielded for X-ray radiation. This is entirely a function of high voltage devices and does not reflect upon the design of the valve.

ENGLISH ELECTRIC VALVE CO. LTD.

ENGLISH ELECTRIC

ANODE CHARACTERISTIC



ENGLISH ELECTRIC VALVE CO. LTD.

HIGH VACUUM RECTIFIER

A296


June 1962

Page 3

ENGLISH ELECTRIC

OUTLINE

927



Ref.	Inches	Millimetres
A	9.850 Max	250 Max
B	5.200 Max	132.1 Max
C	4.000	101.6
D	2.687 Min	68.25 Min
E	2.500 (ref.)	63.50 (ref.)
F	1.339	34.01
G	0.187	4.750
H	0.500	12.7
J	0.500	12.7
K	0.750	19.05
L	0.375	9.525

Millimetre dimensions have been derived from inches.

ENGLISH ELECTRIC VALVE CO. LTD.

CHELMSFORD
ENGLAND

Telephone:
Chelmsford 3491